

BOLT LID TO FRAME w/ (6) 1/2-13 X 2 1/4
STNLS. STL. HEX HD. BOLT W/ WASHERS

MACHINE GROOVE IN SEAT FOR
OIL RESISTANT T-GASKET, NITRILE
60 DUROMETER (HDWR. #02798)

(2) CONCEALED PICKHOLES
PER NF-22642

TYPE "C" CHECKERED TOP DESIGN
w/ PERMAGRIP SURFACE TEXTURE

32 1/4" [819mm]
32" [813mm]
1 1/2" [38mm] LID
WITHOUT GASKET
1 5/8" FRAME
[41mm]
7"
[178mm]

30" [762mm]
36 1/2" [927mm]
46" [1168mm]

NOTE: ALL DIMENSIONS SHOWN ARE IN ENGLISH AND [METRIC].
CAPABLE OF H-25/HS-25 LOAD RATING
COMPONENT NO'S: FRAME 1916-0291; LID 1916-0323
MATERIAL: CAST GRAY IRON ASTM A-48, CLASS 35B
FINISH: NO PAINT
WEIGHT: FRAME 358#; LID 269#

3	03-07-16	ADDED LOAD NOTE	HSH
2	6-14-95	REVISED FRAME "A" DIM, WAS 32 1/8"	ELR
1	4-22-95	CORRECT FRAME AND LID DIMS	CSK
1	DATE	REVISION	INT

DR.	CSK	SCALE	TITLE:	
CH.		1/8"=1"	R-1916-H FRAME AND LID BOLTED AND GASKETED w/ "T" SEAL	
APP.		DIM CHK.	NEENAH FOUNDRY COMPANY NEENAH WISCONSIN 54956	
DATE	4-17-95		NF-1916 549	B